Häny Mixing and Injection Technology

High Shear Mixer



The colloidal mixer is particularly suitable for the production of suspensions consisting of water, cement, ultra-fine binder, bentonite, sand, and other materials. A robust mixing tank combined with highly wear-resistant materials in the mixing pump guarantee a long service life and trouble-free operation.



High Shear Mixer

HCM 100

Key features

3D model

- Excellent mixing results thanks to the high turbulence generated by the high-speed mixing pump
- ► Mixing tank with conical bottom and recirculation line
- Automatic lubrication of the shaft seal and lubricated 3-way valve for switching between mixing or transfer
- Optional additional mixer for water/cement ratio
 < 0.5 and microcements

Typical applications

- Preparation of suspensions consisting of water, cement, ultra-fine binder, bentonite, sand, and other materials
- As a stand-alone system or in combination with agitator and injection pump



High shear mixer	
 Mixing pump:	TMP 9
Approx. capacity ¹ :	2 m³/h
Circulation capacity:	540 I/min
Usable content:	100 I
Max. aggregate size:	5 mm
Liquid temperature:	Max. 40°C
Water connection:	BSP 3/4"

Optional

- Water meter 3/4" for exact water dosing (manual shut-off)
- Automatic water meter 3/4" with adjustable counter for exact water dosing
- Auxiliary mixing unit 3x 400/460 V, 50/60 Hz (3.0/3.6 kW)

^{1:} Water to cement ratio = 1



Electrical data		
Voltage:	3x 400/460 V	
Frequency:	50 / 60 Hz	
Nominal power:	3.0 / 3.6 kW	
Nominal current:	6.15 / 6.45 A	
Speed:	1,440 / 1,695 min ⁻¹	

\	Weight and dimensions		
	Approx. weight:	130 kg	
	Width:	675 mm	
	Height:	1,335 mm	
	Length:	814 mm	

Design and dimensions





