Häny Mixing and Injection Technology

High Shear Mixer HCM 300

The colloidal mixer is particularly suitable for the production of suspensions consisting of water, cement, ultra-fine binder, bentonite, sand, and other materials. A robust mixing tank combined with highly wear-resistant materials in the mixing pump guarantee a long service life and trouble-free operation.



High Shear Mixer

HCM 300

Key features

3D model

- Excellent mixing results thanks to the high turbulence generated by the high-speed mixing pump
- Mixing tank with conical bottom and recirculation line
- Automatic lubrication of the shaft seal and lubricated 3-way valve for switching between mixing or transfer
- Optional additional mixer for water/cement ratio
 < 0.5 and microcements

Typical applications

- Preparation of suspensions consisting of water, cement, ultra-fine binder, bentonite, sand, and other materials
- As a stand-alone system or in combination with agitator and injection pump



High shear mixer			
Mixing pump:			
A m. m. m. a. m. m. m. i. i. i. i. i. i.			

Mixing pump:	TMP 22
Approx. capacity ¹ :	5 m³/h
Circulation capacity:	1,400 l/min
Usable content:	260 I
Max. aggregate size:	8 mm
Liquid temperature:	Max. 40°C
Water connection:	1" BSP

Optional

- Water meter 1" for exact water dosing (manual shut-off)
- Automatic water meter 1" with adjustable counter for exact water dosing
- Auxiliary mixing unit 3x 400/460 V, 50/60 Hz (3.0/3.6 kW)

^{1:} Water to cement ratio = 1



Electrical data				
Voltage:	3x 400/460 V			
Frequency:	50 / 60 Hz			
Nominal power:	9.2 / 10.5 kW			
Nominal current:	16.8 / 17.6 A			
Speed:	1,465 / 1,765 min ⁻¹			

V	Weight and dimensions		
	Approx. weight:	325 kg	
	Width:	925 mm	
	Height:	1,395 mm	
	Length:	1,225 mm	

Design and dimensions





