Häny Mixing and Injection Technology

# High Shear Mixer HCM 600

The colloidal mixer is particularly suitable for the production of suspensions consisting of water, cement, ultra-fine binder, bentonite, sand, and other materials. A robust mixing tank combined with highly wear-resistant materials in the mixing pump guarantee a long service life and trouble-free operation.



## **High Shear Mixer**

### **HCM 600**

#### Key features

#### 3D model

- Excellent mixing results thanks to the high turbulence generated by the high-speed mixing pump
- Mixing tank with conical bottom and recirculation line
- Automatic lubrication of the shaft seal and lubricated 3-way valve for switching between mixing or transfer
- Optional additional mixer for water/cement ratio
   < 0.5 and microcements</li>

#### Typical applications

- Preparation of suspensions consisting of water, cement, ultra-fine binder, bentonite, sand, and other materials
- As a stand-alone system or in combination with agitator and injection pump



High shear mixer	
Mixing pump:	TMP 22
Approx. capacity <sup>1</sup> :	8 m³/h
Circulation capacity:	1,400 l/min
Usable content:	550 I
Max. aggregate size:	8 mm
Liquid temperature:	Max. 40°C
Water connection:	BSP 1½"
	Mixing pump: Approx. capacity¹: Circulation capacity: Usable content: Max. aggregate size: Liquid temperature:

#### Optional

- Water meter 1½" for exact water dosing (manual shut-off)
- Automatic water meter 1½" with adjustable counter for exact water dosing
- Auxiliary mixing unit 3x 400/460 V, 50/60 Hz (3.0/3.6 kW)

<sup>1:</sup> Water to cement ratio = 1



Ele	ctrical data	
Vol	tage:	3x 400/460 V
Fre	quency:	50 / 60 Hz
Noi	minal power:	9.2 / 10.5 kW
Noi	minal current:	16.8 / 17.6 A
Spe	eed:	1,465 / 1,765 min <sup>-1</sup>

7	Weight and dimensions		
_	Approx. weight:	370 kg	
_	Width:	1,025 mm	
_	Height:	1,750 mm	
_	Length:	1,360 mm	
_			

#### Design and dimensions







