



Grout Pump

ZMP 611

Key features

- Nump performance
- Extremely compact vertical injection pump for space-saving installation
- Infinitely variable limitation of injection pressure and delivery rate
- ► High reliability and low-maintenance operation with good accessibility to the wear parts
- ► Fast suction stroke to prevent clogging by flushing the valves
- Cooling water connection for continuous operation and high ambient temperatures

Typical applications

- Injection of anchors, soil nails, and tension cables, as well as for sleeve pipes, rock, and contact injections
- Pre- and post-injections, pumping of bentonite suspensions for pipe and microtunnel driving and filling of pea gravel

	35	Low pressure
Output [l/min]	30	High pressure
	25	
	20	
	15	
	10	
	5	
	0	0 10 20 30 40 50 60 70 80
		Pressure [bar]

	_			
V.	Gra	ш	nı	ımn

Plunger Ø:	65 mm
Capacity ¹ :	2 m³/h
Max. pressure:	75 bar
Min. pressure:	3 bar
Volume per stroke ² :	0.82 I
Max. aggregate size:	5 mm
Hydraulic tank:	52 I
Pump module:	single
Cooling water flow rate:	2–3 l/min
Cooling water connection:	BSP ¾"
Pressure connection:	BSP 1"
Suction connection:	BSP 1½"

Included as standard

- · Manual pressure and flow control
- Oil level, temperature, and filter contamination indicator

Control

PLC
Lockable main switch, emergency stop
Pump ON-OFF

Optional

- · Remote control
- Data logging for pressure and flow rate

¹ Water to cement ratio = 1

² Filling ratio = 100%



Electrical data		
 Voltage:	3x 400/460	
Frequency:	50 / 60 Hz	
Nominal power:	5.5 / 6.3 kW	

Weight and dimensions	7
weight and uninchalona	
Approx. weight: 270 kg	
Width: 510 mm	
Height: 1,410 mm	
Length: 758 mm	_

Construction and dimensions







